

AMENDED CLAIMS

[Received by the International Bureau on 22 April 2004 (22.04.04):
original claims 1 to 7 replaced by amended claims 1 to 5 (1 page)]

1. Equipment for change of rotary gobos comprising a carrier disc
5 provided with circular apertures (9) allowing for lighting of gobos and
furnished with resilient holding means to support interchangeable segments
with the gobos, **characterised in**, that each segment (2) is provided with
a lamella (3) for attachment in the holding means and with means for setting
the segment (2) on the carrier disc (1).
- 10
2. Equipment for a change of rotary gobos according to claim 1, **characterised
in**, that the holding means comprise a system of flexible fingers (10) in a fan-
shaped arrangement, the fingers (10) being at inside ends fixed to the carrier
disc (1) and on the outside free ends adapted to allow for insertion of the
15 segment lamellas (3) between the fingers (10) and the carrier disc (1).
3. Equipment for a change of rotary gobos according to claim 2,
characterised in, that the fingers (10) are at their inside ends integrated into
one unit, while the number of fingers (10) within this unit corresponds to the
20 number of segments (2) to be supported by the carrier disc (1).
4. Equipment for a change of rotary gobos according to claim 1,
characterised in, that each segment (2) is provided with a bearing supporting
a driver (6) with a gobo, the bearing inside ring being provided for by the
25 driver (6) outer rim and the bearing outside ring (5) being attached to the
segment lamella (3) by dismountable-connection means, while the driver (6)
comprise a flange (7) with a spur toothing.
5. Equipment for a change of rotary gobos according to claim 1 or 4,
30 **characterised in**, that the means for setting the segment (2) on the carrier
disc (1) comprise dismountable-connection means for attachment of the
gobo bearing outer ring (5) on the lamella (3).